

TICOL[®] TEAK BRIGHTENER

TB-301

TEAK BRIGHTENER

Product Identification

TICOL[®] Teak Brightener is formulated for the maintenance of hardwoods like teak, irecco and etc. Preferably it should be applied after TICOL[®] Teak Cleaner to further clean the pores and refresh the color of the substrate. It can be used on decking (boat, pool), building elements, flooring and outdoor furniture made up of hardwood.

Application Recommendations

Ready-to use, no need for further thinning. Stir well before use. Application by brush, sponge or cloth is advised. In order to achieve deep cleaning in the pores, brushing will be necessary. Rinse the surface well after use.

Application Amount

Application amount can differ according to the type of the wood, condition of the surfaces, level of aging after previous maintenance. 15 – 18 sq. meters of area can be treated with 1 Liter of material.

Drying time

Technical Properties

Non volatiles, weight %	5 ± 2
Density, gr/cm ³ @20°C	1,01 ± 3

TICOL[®] TEAK BRIGHTENER

Notes

Prior to the application, the surfaces should be free from dust. Pre-treatment with TICOL[®] Teak Cleaner is suggested. After a few minutes, the surfaces should be rinsed well. Contains weak organic acid, therefore the metal accessories should be masked or rinsed before and after the application.

Safety and Storage

Taking necessary precautions stated in the safety data sheet (MSDS) and assuring good ventilation during application is the responsibility of the user. Follow the information on the labels and the MSDS.

In the original, closed cans, under cool and dry stocking conditions (above 5 °C), expiry date is three years after the production.

Packing

0,50 L (PET), 1,0 L (PET), 5 L (PE), and 20 L (PE)

This data sheet, revises any other data sheet issued older than this one. Data enclosed, specifications and recommendations are made according to either international test standards or under specified / controlled, experienced application conditions. It is recommended to test the validity and conformity of those in beforehand. The manufacturer can make revisions on the product without any notice. Unless revised, this Technical Data Sheet is valid for 5 years.